

COMMERCIAL FISHING WIRE ROPES




COMMERCIAL FISHING


SIZE ROPE DIAMETER	6X7 PPC IPS GALVANIZED		6X19/26 PPC IPS/EIPS	
	Approx. Weight per Foot in Pounds	Min. Breaking Strength in Pounds	Approx. Weight per Foot in Pounds	Min. Breaking Strength in Pounds
1/4"	0.094	4,760	0.105	4,940
5/16"	0.15	7,380	0.164	7,660
3/8"	0.21	10,540	0.236	10,980
7/16"	0.29	14,280	0.320	14,880
1/2"	0.38	18,540	0.420	19,260
9/16"	0.48	23,400	0.530	24,300
5/8"	0.59	28,600	0.660	30,000
11/16"	-	-	0.810	36,300
3/4"	0.84	40,800	0.950	42,800
13/16"	-	-	1.110	50,010
7/8"	1.15	53,800	1.290	58,000
1"	1.50	69,600	1.680	75,200
1-1/8"	1.90	87,400	2.130	94,600

TRAWLMASTER


"The brand fishermen ask for by name."



6x7 PPC IPS Galvanized




6x19S IPS Galvanized



6x26 WS PPC EIPS Galvanized

SIZE ROPE DIAMETER	6X19S COMPACTED STRAND PPC GALVANIZED	
	Approx. Weight per Foot in Pounds	Min. Breaking Strength in Pounds
10 MM	0.40	15,400
12 MM	0.45	22,100
13 MM	0.53	25,800
14 MM	0.58	30,600
16 MM	0.723	39,500
18 MM	0.915	49,800
20 MM	1.11	61,500
22 MM	1.26	74,500
24 MM	1.56	88,600
26 MM	1.76	102,500
28 MM	2.04	122,600

BLUEMASTER COMPACTED STRAND



6x19S Compacted Strand PPC Galvanized