

GALVANIZED CABLE




 **M&G**
Industries

GALVANIZED CABLE




1X7/1X19 GALVANIZED CABLE

SIZE ROPE DIAMETER	1X7 GALVANIZED CABLE		1X19 GALVANIZED CABLE	
	Weight per 1000 Ft/lb	Min. Breaking Strength/lb	Weight per 1000 Ft/lb	Min. Breaking Strength/lb
1/64"	0.06	40	-	-
1/23"	0.25	185	-	-
3/64"	0.55	375	-	-
1/16"	0.85	500	0.85	500
5/64"	14.0	800	14.0	-
3/32"	20.0	1,200	20.0	1,200
7/64"	27.0	1,600	27.0	-
1/8"	35.0	2,100	35.0	2,100
5/32"	-	-	55.0	3,300
3/16"	-	-	77.0	4,700
1/4"	-	-	135.0	8,200
5/16"	-	-	210.0	12,500
3/8"	-	-	300.0	18,000




1x7 Galvanized




1x19 Galvanized

7X7/7X19 GALVANIZED CABLE

SIZE ROPE DIAMETER	7X7 GALVANIZED CABLE		7X19 GALVANIZED CABLE	
	Approx. Weight per Foot in Pounds	Min. Breaking Strength in Pounds	Approx. Weight per Foot in Pounds	Min. Breaking Strength in Pounds
1/16" *	7.5	480	-	-
5/64" *	11.0	650	-	-
3/32" *	16.0	920	17.4	1,000
1/8"	28.5	1,700	29.0	2,000
5/32"	43.0	2,600	45.0	2,800
3/16"	62.0	3,700	65.0	4,200
7/32" *	86.0	4,800	86.0	5,600
1/4" *	106.0	6,100	110.0	7,000
5/16" *	167.0	9,200	173.0	9,800
3/8" *	236.0	13,300	243.0	14,400



7x7 Galvanized



7x19 Galvanized

Minimum Breaking Strength for comparison only. Actual operating loads may vary, but should never exceed recommended design factor or 1/7 of catalog breaking strength.

* Listed for comparison only. Actual Factors vary between 6:1 and 3:1 depending on application.

Read important warnings and information on the inside back cover of this catalog titled Cautions