


STAINLESS STEEL CABLE




STAINLESS STEEL CABLE

TYPE 304 STAINLESS STEEL CABLE

SIZE ROPE DIAMETER	7X7 STAINLESS STEEL CABLE - TYPE 304		7X19 STAINLESS STEEL CABLE - TYPE 304	
	Approx. Weight per Foot in Pounds	Min. Breaking Strength in Pounds	Approx. Weight per Foot in Pounds	Min. Breaking Strength in Pounds
.030"	0.7	110	-	-
3/64"	4.2	270	-	-
1/16"	7.5	480	7.5	480
3/32"	16.0	920	17.0	920
1/8"	28.0	1,760	29.0	1,760
5/32"	43.0	2,400	45.0	2,400
3/16"	62.0	3,700	65.0	3,700
7/32"	86.0	5,000	86.0	5,000
1/4"	106.0	6,400	110.0	6,400
5/16"	173.0	9,000	173.0	9,000
3/8"	243.0	12,000	243.0	12,000




7x7 Stainless Steel




7x19 Stainless Steel

TYPE 316 STAINLESS STEEL CABLE

SIZE ROPE DIAMETER	7X7 STAINLESS STEEL CABLE - TYPE 316		7X19 STAINLESS STEEL CABLE - TYPE 316	
	Approx. Weight per Foot in Pounds	Min. Breaking Strength in Pounds	Approx. Weight per Foot in Pounds	Min. Breaking Strength in Pounds
3/64"	4.2	240	-	-
1/16"	7.5	427	7.5	427
3/32"	16.5	819	16.5	819
1/8"	28.5	1,566	29.0	1,566
3/16"	86.0	3,293	65.0	3,293
1/4"	106.0	5,696	110.0	5,696
9/32"	150.0	6,942	150.0	6,942
5/16"	173.0	8,010	173.0	8,010
3/8"	243.0	10,680	243.0	11,000
7/16"	295	14,507	295	14,507
1/2"	425	18,987	425	20,292



7x7 Stainless Steel



7x19 Stainless Steel

Listed for comparison only. Actual operating loads may vary but should never exceed recommended design factor or 20% of catalog breaking strength.

According to Federal Specifications RR-W-410(current).


All material produced to according to ASTM standards A492

Read important warnings and information on the inside back cover of this catalog titled Cautions.

STAINLESS STEEL CABLE

STAINLESS STEEL CABLE

SIZE ROPE DIAMETER	1X19 STAINLESS STEEL STRAND		
	Approx. Weight per Foot in Pounds	Approx. Weight per Foot in Pounds	
		Type 304	Type 316
1/32"	0.7	150	134
3/64"	7.2	375	297
1/16"	8.5	500	445
5/64	14.0	800	712
3/32"	20.0	1,200	1,068
1/8"	35.0	2,100	1,869
5/32"	55.0	3,300	2,937
4 MM	55.0	3,336	2,965
3/16"	77.0	4,700	4,183
5 MM	80.0	5,212	4,632
7/32"	102.0	6,300	5,607
6 MM	124.0	7,505	6,671
1/4"	135.0	8,200	7,298
7 MM	168.0	10,214	9,079
9/32	170.0	10,406	9,261
5/16"	210.0	12,500	11,125
8 MM	220.0	13,340	11,859
3/8"	300.0	17,500	15,575
10 MM	330.0	20,845	18,528
7/16	375.0	22,500	20,025
12 MM	480.0	30,016	26,680
1/2	540.0	28,220	25,116
14 MM	600.0	40,856	36,317
9/16	690.0	32,190	28,649
5/8	860.0	40,570	36,107
16 MM	860.0	53,363	45,195
3/4 1000	-	51,717	-



1x19 Stainless
Steel Strand

According to Federal Specifications RR-W-410(current).

All material produced to according to ASTM standards A492


Read important warnings and information on the inside back cover of this catalog titled Cautions.

STAINLESS STEEL CABLE



SIZE ROPE DIAMETER	1X7 STAINLESS STEEL 316 COMPACTED STRAND	
	Approx. Weight per 1000 Feet in Pounds	Min. Breaking Strength in Pounds
2 MM	16	974
2.5 MM	25	1,521
3 MM	37	2,205
4 MM	65	3,924


STAINLESS STEEL COMPACTED STRAND



1x7 Stainless Steel 316 Compacted Strand

SIZE ROPE DIAMETER	1X19 STAINLESS STEEL 316 COMPACTED STRAND	
	Approx. Weight per 1000 Feet in Pounds	Min. Breaking Strength in Pounds
5 MM	101	5,379
6 MM	147	7,826
7 MM	195	10,825
8 MM	256	13,558
10 MM	402	21,539
12 MM	544	31,747
14 MM	600	43,416
16 MM	850	45,195
19 MM	1100	70,548

STAINLESS STEEL COMPACTED STRAND



1x19 Stainless Steel 316 Compacted Strand

Read important warnings and information on the inside back cover of this catalog titled Cautions.

All material produced to according to ASTM A492 standards